



6 INCH SKIL SAW

Model "67"

Cuts 1 7/8 in.

A heavy duty saw — more compact and powerful — for use on small homes, garages, etc., and for general remodeling work. Efficient for intermittent factory maintenance sawing, except flooring work. Suitable for scoring tile, concrete, limestone, etc.; practical for tuck-pointing. Will rip and cross-cut hard wood up to 1 in. and cross-cut dressed pine lumber up to 2 in.

EQUIPMENT One combination blade; 10 ft. of 3-conductor rubber covered cord with two-prong connector; steel permanent carrying case; wrench; lubricant.

MODEL "67", each.....\$85.00

SPECIFICATIONS

Blade Diameter: 6 in.

Cutting Capacity: Maximum in wood 1 7/8 in.

Motor: Universal, operates on either D.C. or A.C. up to 60 cycle. Voltage as ordered.

Free Speed of Blade: 3400 R.P.M.

Switch: Two-pole momentary switch in handle, bakelite enclosed.

Base Adjustment: Vertically for depth of cut from 3/4 in.

VOLTAGES: Standard voltage, 115. Also furnished for 220 and odd voltages — no extra cost. Specify voltage desired.

to 1 7/8 in. Also tilts for bevel cuts; at 45° cuts through lumber 1 1/8 in. thick.

Bearings: High grade ball bearings throughout.

Safety: Automatic telescoping guard rotates on ball bearings; shields saw blade when not cutting.

Blower: Keeps line of cut clear of sawdust.

Length Overall: 15 1/2 in.

Net Weight: 12 1/2 lbs.

Shipping Weight: 20 lbs.

7 1/4 INCH SKIL SAW

Model "77"

Cuts 2 3/8 in.

The greatest value among 7 1/4 in. saws. Cross-cuts 2 in. rough lumber and bevel-cuts 2 in. dressed lumber at 45°. Its design provides quicker adjustment for both depth and bevel cutting. Ideal for form work, for maintenance work in industrial plants, for building stock bins and partitions, for cutting freight car bracing timbers. Swiftly cuts metals, stone, concrete, tile and many composition materials.

EQUIPMENT One combination blade; 10 ft. of 3-conductor rubber covered cord with two-prong connector; steel permanent carrying case; wrench; lubricant.

MODEL "77", each.....\$118.00

SPECIFICATIONS

Blade Diameter: 7 1/4 in.

Cutting Capacity: Maximum in wood 2 3/8 in.

Motor: Universal, operates on either D.C. or A.C. up to 60 cycle. Voltage as ordered.

Free Speed of Blade: 3200 R.P.M.

Switch: Two-pole, momentary contact switch in handle, bakelite enclosed.

Base Adjustment: Vertically for depth of cut from 3/4 in. to 2 3/8 in. Also tilts for bevel

VOLTAGES: Standard voltage, 115. Also furnished for 220, 250 and odd voltages — no extra cost. Specify voltage desired.

cuts; at 45° cuts through lumber 1 3/4 in. thick.

Bearings: High grade ball bearings throughout.

Safety: Automatic telescoping guard rotates on ball bearings; shields saw blade when not cutting.

Blower: Keeps line of cut clear of sawdust.

Length Overall: 17 1/4 in.

Net Weight: 18 lbs.

Shipping Weight: 35 lbs.

Accessories are listed on pages 26, 27, 28, 29 and 34.